

INDUSTRIAL GRADE COATED GAFFER'S TAPE

TYPICAL APPLICATIONS

- For A/V, TV, photography, theatrical and motion picture industries to bundle wires, color-code and tape down lighting and props
- Masking silk-screen frames
- Protection and book-binding
- HVAC line set tape


ADVANTAGES AND BENEFITS

- Waterproof backing
- Excellent holding power
- Conformable
- Durable
- Excellent weathering features
- Very high tensile strength

CONSTRUCTION

Overall Grade/Function: Industrial
Backing: Lusterless, vinyl or acrylic coated cloth
Adhesive: Synthetic rubber

COLOR(S)



STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	75 oz/in width	8.21 N/10 mm
Thickness	10.75 mils	0.27 mm
Elongation	4%	4%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P- 628- 03/05/2015

