

PROFESSIONAL GAFFER'S COATED CLOTH TAPE

TYPICAL APPLICATIONS

- Gaffer's applications
- Hold wiring, lighting and props
- Color-coding

ADVANTAGES AND BENEFITS

- High adhesion and tack
- Clean removal
- Conformable
- Hand tearable

CONSTRUCTION

Overall Grade/Function: Professional Gaffer's

Backing: Lusterless, vinyl coated cloth

Adhesive: Synthetic rubber

COLOR(S)



STANDARD WIDTH(S)

24 mm 48 mm 72 mm

STANDARD LENGTH(S)

46 m 55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	11 mils	0.28 mm
Elongation	4%	4%
Application Temperature Range	45 F to 200 F	7 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-1586A

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

