

PREMIUM GAFFER'S COATED CLOTH TAPE

TYPICAL APPLICATIONS

- Waterproof sealing of containers
- Temporary protection from welding spatter
- Holding, bundling and temporary repair

ADVANTAGES AND BENEFITS

- Matte surface
- Abrasion resistant
- Waterproof backing
- High tensile strength

CONSTRUCTION

Overall Grade/Function: Premium Gaffer's

Backing: Acrylic coated cloth

Adhesive: Synthetic rubber

COLOR(S)



STANDARD WIDTH(S)

24 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	70 lbs/in width	122.6 N/10 mm
Adhesion to Stainless Steel	77 oz/in width	8.43 N/10 mm
Thickness	12 mils	0.30 mm
Elongation	6%	6%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-1586A

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P-672-03/12/2015